





Riferimento catena	Dati tecnici
--------------------	--------------

Rif. ISO N°	Codice AS Nord	Passo [mm]	Larghezza interna [mm] MIN	Ø Rullo [mm] MAX	Ø Perno [mm] MAX	Spessore piastra interna [mm]	Spessore piastra esterna [mm]	Altezza piastra [mm]	Lunghezza perno [mm]	Interasse [mm]	Carico di rottura [kN] MIN	Peso [kg/m]
<b>Semplici</b>												
		P	B1	Dr	Dp	S1	S2	G1	L1	K	FB	q
08B-1	08B1C	12,700	7,75	8,51	4,45	1,55	1,55	11,81	17,0	-	17,8	0,70
10B-1	10B1C	15,875	9,65	10,16	5,08	1,55	1,55	14,70	19,6	-	22,2	0,92
12B-1	12B1C	19,050	11,68	12,07	5,72	1,80	1,80	15,93	22,7	-	28,9	1,20
16B-1	16B1C	25,400	17,02	15,88	8,28	4,12	3,10	21,00/24,00	36,1	-	60,0	3,45
20B-1	20B1C	31,750	19,56	19,05	10,19	4,62	3,61	26,42	39,8	-	95,0	3,85
24B-1	24B1C	38,100	25,40	25,40	14,63	6,10	5,08	35,75	53,4	-	160,0	7,45
28B-1	28B1C	44,450	30,99	27,94	15,90	7,62	6,35	41,68	65,1	-	200,0	9,35
32B-1	32B1C	50,800	30,99	29,21	17,81	7,11	6,35	47,60	67,4	-	250,0	10,10
<b>Doppie</b>												
		P	B1	Dr	Dp	S1	S2	G1	L2	K	FB	q
08B-2	08B2C	12,700	7,75	8,51	4,45	1,55	1,55	11,81	31,0	13,92	310,0	1,38
10B-2	10B2C	15,875	9,65	10,16	5,08	1,55	1,55	14,70	36,2	16,59	445,0	1,80
12B-2	12B2C	19,050	11,68	12,07	5,72	1,80	1,80	15,93	42,2	19,46	578,0	2,40
16B-2	16B2C	25,400	17,02	15,88	8,28	4,12	3,10	20,20	68,0	31,88	106,0	5,50
20B-2	20B2C	31,750	19,56	19,05	10,19	4,62	3,61	26,42	76,7	36,45	170,0	7,80
24B-2	24B2C	38,100	25,40	25,40	14,63	6,10	5,08	35,75	101,8	48,36	280,0	14,80
<b>Triple</b>												
		P	B1	Dr	Dp	S1	S2	G1	L3	K	FB	q
08B-3	08B3C	12,700	7,75	8,51	4,45	1,55	1,55	11,81	44,9	13,92	445,0	2,06
16B-3	16B3C	25,400	17,02	15,88	8,28	4,12	3,10	20,20	99,9	31,88	1600,0	10,12

Misure ANSI disponibili su richiesta