


G 26



ACCESSORIES:

- Spring Collecting Link

Chain Ref.	Technical Details											
------------	-------------------	--	--	--	--	--	--	--	--	--	--	--

Ref. ISO N°	AS Nord code	Pitch [mm]	Inside width [mm] MIN	Ø Roller diam. [mm] MAX	Ø Pin diam. [mm] MAX	Plate thickness inner [mm]	Plate thickness outer [mm]	Plate height [mm]	Pin lenght [mm]	Pin lenght cotter / spring conn. link [mm]	ISO606 Tensile strenght [kN] MIN	Weight [kg/m]
-------------	--------------	---------------	-----------------------------	-------------------------------	----------------------------	-------------------------------	-------------------------------	----------------------	--------------------	---	--	------------------

Simple

		P	B1	Dr	Dp	S1	S2	G1	L1	PGC / PGM	FB	q
-	428 OR	12,700	7,75	8,51	4,45	1,80	1,60	11,80	16,7	- / -	23,4	0,88
-	530 SDZ	15,875	9,53	10,30	5,08	2,40	2,60	14,80	25,3	- / -	48,6	1,37
08B-1	08B1OR	12,700	7,75	8,51	4,45	1,60	1,60	11,80	18,8	- / 19,90	20,1	0,74
10B-1	10B1OR	15,875	9,65	10,16	5,08	1,60	1,60	14,15	21,4	- / 22,95	28,5	0,99
12B-1	12B1OR	19,050	11,68	12,07	5,72	1,85	1,85	16,00	24,9	- / 26,80	33,3	1,27
16B-1	16B1OR	25,400	17,02	15,88	8,26	4,00	4,00	20,30	38,9	- / 41,30	73,9	2,78
20B-1	20B1OR	37,750	19,56	19,05	10,19	4,50	4,50	26,40	44,5	- / 48,50	107,4	3,78