


G 26

F 59

F 30

G 58



ACCESSORIES:

- Spring Collecting Link
- Single Cranked Link
- Double Cranked Link
- Cotter Connecting Link

Chain Ref. Technical Details

Ref. ISO N°	AS Nord code	Pitch [mm]	Inside width [mm] MIN	Ø Roller diam. [mm] MAX	Ø Pin diam. [mm] MAX	Plate width inner [mm]	Plate width outer [mm]	Plate height [mm]	Pin length [mm]	Int. [mm]	ISO606 Tensile strenght [kN]	Weight [kg/m]
-------------	--------------	------------	--------------------------	----------------------------	-------------------------	------------------------	------------------------	-------------------	-----------------	-----------	------------------------------	---------------

Simple												
		P	B1	Dr	Dp	S1	S2	G1	L1	K	FB	q
06B-1	06B1ZN	9,525	5,72	6,35	3,28	1,29	1,04	8,20	12,5	-	75,65	0,39
08B-1	08B1ZN	12,700	7,75	8,51	4,45	1,55	1,55	11,70	16,5	-	15,13	0,70
10B-1	10B1ZN	15,875	9,65	10,16	5,08	1,55	1,55	14,60	18,8	-	18,87	0,96
12B-1	12B1ZN	19,050	11,68	12,07	5,72	1,81	1,81	16,00	21,9	-	24,56	1,22
16B-1	16B1ZN	25,400	17,02	15,88	8,28	4,12	3,10	21,08	34,9	-	51,00	2,80
20B-1	20B1ZN	31,750	19,56	19,05	10,19	4,62	3,61	26,42	39,8	-	80,75	3,85
24B-1	24B1ZN	38,100	25,40	25,40	14,63	6,10	5,08	33,40	52,6	-	136,00	7,45

ANSI size available on request