



Chain Ref.	Technical Details									
------------	-------------------	--	--	--	--	--	--	--	--	--

Ref. ISO N°	AS Nord code	Pitch [mm]	Inside width [mm] MIN	Ø Roller diam. [mm] MAX	Ø Pin diam. [mm] MAX	Clip length [mm]	Length [mm]	Profile width [mm]	Clip width [mm]	Profile height [mm]
-------------	--------------	------------	--------------------------	----------------------------	-------------------------	------------------	-------------	--------------------	-----------------	---------------------

Simple

		P	B1	Dr	Dp	LG	LB	F1	L1	HW
08B-1	08BKT	12,700	7,75	8,51	4,45	24,2	23,0	17,0	19,6	12,3
08B-1**	08BKTS	12,700	7,75	8,51	4,45	24,2	23,0	17,0	19,6	12,3
12B-1	12BKT	19,050	11,68	12,07	5,72	35,6	34,2	22,8	25,4	21,0
12B-1**	12BKTS	19,050	11,68	12,07	5,72	35,6	34,2	22,8	25,4	21,0
16B-1	16BKT	25,400	17,02	15,88	8,28	49,0	47,4	32,0	40,4	21,4
16B-1**	16BKTS	25,400	17,02	15,88	8,28	49,0	47,4	32,0	40,4	21,4

\*\*The chain is made of materials resistant to rust and acid.